


Features

- Low THD, 10% Max up to 240 Vac
- Compact Metal Case with Excellent Thermal Performance
- Isolated 0-10V Dimmable
- Input Surge Protection: 4kV line-line, 6kV line-earth
- High Reliability & Long Lifetime: 93,000 hrs. at 75°C Case Temperature
- Suitable for Independent Use and Class I Luminaires
- Input UVP and Input OVP
- Waterproof(IP67)
- 5 Years Warranty



Description

The EUC-040SxxxDVM000x series is a 40W, constant-current IP67 LED driver that operates from 90-305 Vac input with excellent power factor. It is created for many lighting applications including low bay, tunnel and street. The high efficiency of these drivers and compact metal case enable them to run cooler, significantly improving reliability and extending product life. To ensure trouble-free operation, protection is provided against input surge, input under voltage, input over voltage, output over voltage, short circuit, and over temperature.

Models

Output Current	Input Voltage Range(1)	Output Voltage Range	Max. Output Power	Typical Efficiency (2)	Power Factor		Model Number
					120Vac	220Vac	
500 mA	90 ~ 305 Vac 127 ~ 250 Vdc	40 ~ 80 Vdc	40 W	87%	0.99	0.96	EUC-040S070DVM0004
700 mA	90 ~ 305 Vac 127 ~ 250 Vdc	32 ~ 57 Vdc	40 W	86%	0.99	0.96	EUC-040S070DVM
860 mA	90 ~ 305 Vac 127 ~ 250 Vdc	23 ~ 47 Vdc	40 W	86%	0.99	0.96	EUC-040S105DVM0004
1050 mA	90 ~ 305 Vac 127 ~ 250 Vdc	21 ~ 38 Vdc	40 W	85%	0.99	0.96	EUC-040S105DVM

Notes: (1) Certified input voltage range: 120-240Vac/127-250Vdc.

(2) Measured at 100% load and 220 Vac input.

Input Specifications

Parameter	Min.	Typ.	Max.	Notes
Input Voltage	90 Vac	-	305 Vac	127 ~ 250 Vdc
Input Frequency	47 Hz	-	63 Hz	
Leakage Current	-	-	0.70 mA	IEC60598-1; 240Vac/ 60Hz
Input AC Current	-	-	0.55 A	Measured at 100% load and 120 Vac input.
	-	-	0.30 A	Measured at 100% load and 220 Vac input.

Input Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Inrush Current(I ² t)	-	-	0.01 A ² s	At 220Vac input, 25°C cold start, duration= 36 μs, 10%Ipk-10%Ipk. See Inrush Current Waveform for the details.
Power Factor	0.90	-	-	120-240Vac, 50~60Hz, 75%-100%load (30~40W)
THD	-	-	15%	
THD	-	-	10%	200-240Vac, 50~60Hz, 75%-100%load (30~40W)

Output Specifications

Parameter	Min.	Typ.	Max.	Notes
Output Current Tolerance	-8%lo	-	8%lo	
Total Output Current Ripple (pk-avg)	-	50%lo	75%lo	At 100% load condition
Output Current Overshoot / Undershoot	-	5%lo	10%lo	At 100% load condition
No Load Output Voltage				
EUC-040S070DVM0004	-	-	100V	
EUC-040S070DVM	-	-	100V	
EUC-040S105DVM0004	-	-	80V	
EUC-040S105DVM	-	-	80V	
Line Regulation	-	-	±5.0%	Measured at 100% load
Load Regulation	-	-	±5.0%	
Turn-on Delay Time	-	1.5 s	2.0 s	Measured at 120Vac input, 75%-100% load
	-	1.0 s	1.5 s	Measured at 220Vac input, 75%-100% load
Temperature Coefficient of I _{max}	-	0.06%/°C	-	Case temperature = 0°C ~T _c max

Note: All specifications are tested by Cree XLamp XP-G and typical at 25°C unless otherwise stated.

General Specifications

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 120 Vac input:				Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 1.0% lower if measured immediately after startup.)
EUC-040S070DVM0004	84.0%	85.0%	-	
EUC-040S070DVM	83.0%	84.0%	-	
EUC-040S105DVM0004	83.0%	84.0%	-	
EUC-040S105DVM	82.0%	83.0%	-	
Efficiency at 220 Vac input:				Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 1.0% lower if measured immediately after startup.)
EUC-040S070DVM0004	86.0%	87.0%	-	
EUC-040S070DVM	85.0%	86.0%	-	
EUC-040S105DVM0004	85.0%	86.0%	-	
EUC-040S105DVM	84.0%	85.0%	-	

General Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 277 Vac input: EUC-040S070DVM0004 EUC-040S070DVM EUC-040S105DVM0004 EUC-040S105DVM	86.0% 85.0% 85.0% 84.0%	87.0% 86.0% 86.0% 85.0%	- - - -	Measured at 100% load and steady-state temperature in 25°C ambient; (Efficiency will be about 1.0% lower if measured immediately after startup.)
MTBF	-	598,000 Hours	-	Measured at 220Vac input, 80%Load and 25°C ambient temperature (MIL-HDBK-217F)
Lifetime	-	93,000 Hours	-	Measured at 120Vac input, 80%Load and 75°C case temperature; See lifetime vs. Tc curve for the details
Operating Case Temperature for Safety Tc_s	-40 °C	-	+90 °C	
Operating Case Temperature for Warranty Tc_w	-40 °C	-	+75 °C	Case temperature for 5 years warranty. Humidity: 10% RH to 100% RH.
Storage Temperature	-40 °C	-	+85 °C	Humidity: 5% RH to 100% RH.
Dimensions Inches (L × W × H) Millimeters (L × W × H)	3.46 x 2.52 x 1.26 88 x 64 x 32			With mounting ear 4.13 x 2.52 x 1.26 105 x 64 x 32
Net Weight	-	375 g	-	

Note: All specifications are tested by Cree XLamp XP-G and typical at 25°C unless otherwise stated.

Dimming Specifications

Parameter	Min.	Typ.	Max.	Notes
Absolute Maximum Voltage on the 0~10V Input Pin	-20 V	-	+20 V	
Source Current on 0~10V Input Pin	0 µA	200 µA	250 µA	
Dimming Output Range	10%Iomax	-	100%Iomax	
Recommended Dimming Input Range	0 V	-	10 V	

Safety & EMC Compliance


Safety Category	Standard
CE	EN 61347-1, EN61347-2-13
CCC	GB 19510.1, GB 19510.14
KS	KS C 7655
EMI Standards	Notes
EN 55015 ⁽¹⁾	Conducted emission Test & Radiated emission Test

Safety & EMC Compliance (Continued)


EMI Standards	Notes
EN 61000-3-2	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
EMS Standards	Notes
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS
EN 61000-4-4	Electrical Fast Transient / Burst-EFT
EN 61000-4-5	Surge Immunity Test: AC Power Line: line to line 4 kV, line to earth 6 kV
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Requirements Applies To Lighting Equipment

Note: (1) This LED driver meets the EMI specifications above, but EMI performance of a luminaire that contains it depends also on the other devices connected to the driver and on the fixture itself.


Derating



Lifetime vs. Case Temperature




Inrush Current Waveform




Efficiency vs. Load


EUC-040S070DVM ($I_o=700mA$)
Efficiency vs. Output Voltage




EUC-040S070DVM0004 ($I_o=500mA$)
Efficiency vs. Output Voltage



EUC-040S105DVM ($I_o=1050mA$)
Efficiency vs. Output Voltage




EUC-040S105DVM0004 ($I_o=860mA$)
Efficiency vs. Output Voltage




Power Factor

PF vs. Load




Total Harmonic Distortion



Protection Functions

Parameter		Min.	Typ.	Max.	Notes
Over Voltage Protection		Limits output voltage at no load and in case the normal voltage limit fails.			
Short Circuit Protection		Auto Recovery. No damage shall occur when any output operating in a short circuit condition. The power supply shall be self-recovery when the fault condition is removed.			
Over Temperature Protection		Decreases output current. Returning to normal after over temperature is removed.			
Input Under Voltage Protection		Auto Recovery. Turn off the output when the input voltage falls below $83 \pm 10V$. And the driver will restart when the input voltage exceeds $88 \pm 10V$.			
Input Over Voltage Protection	Input Protection Voltage	330 Vac	340 Vac	350 Vac	Turn off the output when the input voltage exceeds protection voltage.
	Recovery Voltage	300 Vac	320 Vac	340 Vac	Auto Recovery. The driver will restart when the input voltage falls below recovery voltage.
	Max. of Input Over Voltage	-	-	380 Vac	


● Input Over Voltage Protection Diagram



Dimming

● 0-10V Dimming

The recommended implementation is provided below.




Implementation 1: DC Input

Notes:

1. The dimmer can also be replaced by an active 0-10V voltage source signal or passive components like resistors and zener.
2. Do not connect Dim- to the output V- or V+, otherwise the driver will not work properly.
3. If 0-10V dimming is not used, Dim+ should be open.

Mechanical Outline



RoHS Compliance

Our products comply with the European Directive 2011/65/EU, calling for the elimination of lead and other hazardous substances from electronic products.

Revision History

Change Date	Rev.	Description of Change		
		Item	From	To
2016-12-30	A	Datasheet Release	/	/
2017-08-29	B	Features	/	Updated
		Input Voltage Range(Vac)	108 ~ 305 Vac	90 ~ 305 Vac
		Dimming Specifications - Absolute Maximum Voltage on the 0~10V Input Pin	Min.=0V	Min.= -20V
		Derating Curve	/	Added
		Dimming - 0-10V Dimming - Implementation 1: DC Input	/	Corrected
		Dimming - 0-10V Dimming - Implementation 2: External Resistor	/	Deleted
2018-03-23	C	Description	/	Updated
		MTBF	732,000 Hours	598,000 Hours
		Safety & EMC Compliance - Safety Category - CCC	/	Added