

Features

- Ultra High Efficiency (Up to 95%)
- Full Power at Wide Output Current Range (Constant Power)
- Thermal Sensing and Protection for LED Module
- DALI/Timer Dimmable (3 Timer Modes)
- Dim-to-Off with Standby Power ≤ 0.5 W
- Always-on Auxiliary Power: 12Vdc, 200mA
- Output Lumen Compensation
- Input Surge Protection: 6kV line-line, 10kV line-earth
- All-Around Protection: OVP, SCP, OTP
- Waterproof (IP67) and UL Dry / Damp / Wet Location
- SELV Output
- TYPE HL, for use in a Class I, Division 2 hazardous (Classified) location
- 7 Years Warranty



Description

The EUD-600SxxxBT series is a 600W, constant-current, programmable LED driver that operates from 90-305 Vac input with excellent power factor. Created for many lighting applications including high bay, sports and horticultural, it provides a dim-to-off mode with low standby power. The high efficiency of these drivers and compact metal case enables them to run cooler, significantly improving reliability and extending product life. To ensure trouble-free operation, protection is provided against input surge, output over voltage, short circuit, and over temperature.

Models

Adjustable Output Current Range	Full-Power Current Range (1)	Default Output Current	Input Voltage Range(2)	Output Voltage Range	Max. Output Power	Typical Efficiency (3)	Power Factor		Model Number
							120Vac	220Vac	
0.224-2.80A	2.24-2.80A	2.8 A	90~305Vac/ 127~300Vdc	108 ~ 268Vdc	600 W	95.0%	0.99	0.96	EUD-600S280BT
0.336-4.20A	3.36-4.20A	4.2 A	90~305Vac/ 127~300Vdc	72 ~ 178Vdc	600 W	94.5%	0.99	0.96	EUD-600S420BT
0.448-5.60A	4.48-5.60A	5.6 A	90~305Vac/ 127~300Vdc	54 ~ 134Vdc	600 W	94.5%	0.99	0.96	EUD-600S560BT
0.592-7.40A	5.92-7.40A	7.0 A	90~305Vac/ 127~300Vdc	41 ~ 101Vdc	600 W	94.0%	0.99	0.96	EUD-600S740BT ⁽⁴⁾
0.784-9.80A	7.84-9.80A	9.8 A	90~305Vac/ 127~300Vdc	31 ~ 76Vdc	600 W	94.0%	0.99	0.96	EUD-600S980BT ⁽⁴⁾

Notes: (1) Output current range with constant power at 600W


(2) Certified input voltage range: UL, FCC 100-277Vac or 127-300Vdc; otherwise 100-240Vac or 127-250Vdc

(3) Measured at full load and 220Vac input (see below "General Specifications" for details).


(4) SELV Output

I-V Operating Area


EUD-600S280BT




EUD-600S420BT




EUD-600S560BT



EUD-600S740BT



EUD-600S980BT



Input Specifications

Parameter	Min.	Typ.	Max.	Notes
Input Voltage	90 Vac	-	305 Vac	127-300Vdc
Input Frequency	47 Hz	-	63 Hz	
Leakage Current	-	-	0.75 MIU	UL8750; 277Vac/ 60Hz, grounding effectively
	-	-	0.70 mA	IEC60598-1; 240Vac/ 60Hz, grounding effectively
Input AC Current	-	-	6.0 A	Measured at full load and 120 Vac input.
	-	-	3.5 A	Measured at full load and 220 Vac input.
Inrush Current(I^2t)	-	-	4.70 A ² s	At 220Vac input, 25°C cold start, duration=7.64 ms, 10%Ipk-10%Ipk. See Inrush Current Waveform for the details.
PF	0.90	-	-	At 100-277Vac, 50-60Hz, 60%-100% Load (360 - 600W)
THD	-	-	20%	
THD	-	-	10%	At 220-240Vac, 50-60Hz, 75%-100% Load (450 - 600W)

Output Specifications

Parameter	Min.	Typ.	Max.	Notes
Output Current Tolerance	-5%loset	-	5%loset	At full load condition
Output Current Setting(loset) Range				
EUD-600S280BT	224 mA	-	2800 mA	
EUD-600S420BT	336 mA	-	4200 mA	
EUD-600S560BT	448 mA	-	5600 mA	
EUD-600S740BT	592 mA	-	7400 mA	
EUD-600S980BT	784 mA	-	9800 mA	
Output Current Setting Range with Constant Power				
EUD-600S280BT	2240 mA	-	2800 mA	
EUD-600S420BT	3360 mA	-	4200 mA	
EUD-600S560BT	4480 mA	-	5600 mA	
EUD-600S740BT	5920 mA	-	7400 mA	
EUD-600S980BT	7840 mA	-	9800 mA	
Total Output Current Ripple (pk-pk)	-	5%lomax	10%lomax	At full load condition, 20 MHz BW
Output Current Ripple at < 200 Hz (pk-pk)	-	2%lomax	-	At full load condition. Only this component of ripple is associated with visible flicker.
Startup Overshoot Current	-	-	10%lomax	At full load condition
No Load Output Voltage				
EUD-600S280BT	-	290 V	295 V	
EUD-600S420BT	-	190 V	200 V	
EUD-600S560BT	-	150 V	155 V	
EUD-600S740BT	-	118 V	120 V	
EUD-600S980BT	-	87 V	95 V	
Line Regulation	-	-	±0.5%	Measured at full load
Load Regulation	-	-	±1.5%	

Output Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Turn-on Delay Time	-	-	1.0 s	Measured at 120Vac input, 60%-100% Load
	-	-	0.5 s	Measured at 220Vac input, 60%-100% Load
Temperature Coefficient of I _o set	-	0.03%/°C	-	Case temperature = 0°C ~T _c max
12V Auxiliary Output Voltage	10.8 V	12 V	13.2 V	
12V Auxiliary Output Source Current	0 mA	-	200 mA	Return terminal is "OTP--"

Note: All specifications are typical at 25°C unless otherwise stated.

General Specifications

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 120 Vac input: EUD-600S280BT I _o = 2240 mA I _o = 2800 mA EUD-600S420BT I _o = 3360 mA I _o = 4200 mA EUD-600S560BT I _o = 4480 mA I _o = 5600 mA EUD-600S740BT I _o = 5920 mA I _o = 7400 mA EUD-600S980BT I _o = 7840 mA I _o = 9800 mA	91.0% 90.0% 90.5% 89.5% 90.0% 89.5% 89.5% 89.0% 90.0% 89.5%	93.0% 92.0% 92.5% 91.5% 92.0% 91.5% 91.5% 91.0% 92.0% 91.5%	- - - - - - - - - -	Measured at full load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
Efficiency at 220 Vac input: EUD-600S280BT I _o = 2240 mA I _o = 2800 mA EUD-600S420BT I _o = 3360 mA I _o = 4200 mA EUD-600S560BT I _o = 4480 mA I _o = 5600 mA EUD-600S740BT I _o = 5920 mA I _o = 7400 mA EUD-600S980BT I _o = 7840 mA I _o = 9800 mA	93.0% 92.5% 92.5% 92.0% 92.5% 92.0% 92.0% 91.5% 92.0% 91.0%	95.0% 94.5% 94.5% 94.0% 94.5% 94.0% 94.0% 93.5% 94.0% 93.0%	- - - - - - - - - -	Measured at full load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)

General Specifications (Continued)

Parameter	Min.	Typ.	Max.	Notes
Efficiency at 277 Vac input: EUD-600S280BT Io= 2240 mA Io= 2800 mA EUD-600S420BT Io= 3360 mA Io= 4200 mA EUD-600S560BT Io= 4480 mA Io= 5600 mA EUD-600S740BT Io= 5920 mA Io= 7400 mA EUD-600S980BT Io= 7840 mA Io= 9800 mA	93.0% 92.5%	95.0% 94.5%	- -	Measured at full load and steady-state temperature in 25°C ambient; (Efficiency will be about 2.0% lower if measured immediately after startup.)
Standby power	-	-	0.5 W	
MTBF	-	200,000 Hours	-	
Lifetime	-	108,000 Hours	-	
Operating Case Temperature for Safety Tc_s	-40°C	-	+89°C	
Operating Case Temperature for Warranty Tc_w	-40°C	-	+75°C	
Storage Temperature	-40°C	-	+85°C	
Dimensions Inches (L × W × H) Millimeters (L × W × H)	9.84 × 5.67 × 1.91 250 × 144 × 48.5			
Net Weight	-	3515 g	-	

Note: All specifications are typical at 25°C unless otherwise stated.

Dimming Specifications

Parameter	Min.	Typ.	Max.	Notes
DA, DA High Level	9.5V	16V	22.5V	
DA, DA Low Level	-6.5V	0V	6.5V	
DA, DA Current	0mA	-	2mA	

Dimming Specifications (Continued)

Parameter		Min.	Typ.	Max.	Notes
Dimming Output Range	EUD-600S280BT EUD-600S420BT EUD-600S560BT EUD-600S740BT EUD-600S980BT	10%loset	-	loset	2240 mA ≤ loiset ≤ 2800 mA 3360 mA ≤ loiset ≤ 4200 mA 4480 mA ≤ loiset ≤ 5600 mA 5920 mA ≤ loiset ≤ 7400 mA 7840 mA ≤ loiset ≤ 9800 mA
	EUD-600S280BT EUD-600S420BT EUD-600S560BT EUD-600S740BT EUD-600S980BT	224 mA 336 mA 448 mA 592 mA 784 mA	-	loiset	224 mA ≤ loiset < 2240 mA 336 mA ≤ loiset < 3360 mA 448 mA ≤ loiset < 4480 mA 592 mA ≤ loiset < 5920 mA 784 mA ≤ loiset < 7840 mA

Note: All specifications are typical at 25 °C unless stated otherwise.


Standards Compliance

Safety Category	Standard
UL/CUL	UL8750,CAN/CSA-C22.2 No. 250.13
CE	EN 61347-1, EN61347-2-13
EMI Standards	Notes
EN 55015 ⁽¹⁾	Conducted emission Test & Radiated emission Test
EN 61000-3-2	Harmonic current emissions
EN 61000-3-3	Voltage fluctuations & flicker
FCC Part 15 ⁽¹⁾	ANSI C63.4 Class B
	This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: [1] this device may not cause harmful interference, and [2] this device must accept any interference received, including interference that may cause undesired Operation.
EMS Standards	Notes
EN 61000-4-2	Electrostatic Discharge (ESD): 8 kV air discharge, 4 kV contact discharge
EN 61000-4-3	Radio-Frequency Electromagnetic Field Susceptibility Test-RS
EN 61000-4-4	Electrical Fast Transient / Burst-EFT
EN 61000-4-5	Surge Immunity Test: AC Power Line: line to line 6 kV, line to earth 10 kV ⁽²⁾
EN 61000-4-6	Conducted Radio Frequency Disturbances Test-CS
EN 61000-4-8	Power Frequency Magnetic Field Test
EN 61000-4-11	Voltage Dips
EN 61547	Electromagnetic Immunity Requirements Applies To Lighting Equipment
DALI Standards	Notes
DALI	IEC62386-101,102 & part of 207 ⁽³⁾


Note: (1) This LED driver meets the EMI specifications above, but EMI performance of a luminaire that contains it depends also on the other devices connected to the driver and on the fixture itself.

- (2) To perform electric strength (hi-pot) testing, the “GDT ground disconnect” (nut and metal lock sheet) on the driver end-cap should be removed temporarily to prevent the internal gas discharge tube from conducting (as allowed by IEC 60598-1 Clause 10.2). After testing is completed, these items must be reinstalled to restore line-to-earth surge protection and secure the end cap.
- (3) Optional Commands Implemented: 242 (query short circuit), 243 (query open circuit)


Derating







Lifetime vs. Case Temperature









Inrush Current Waveform




Efficiency vs. Load






Power Factor



Total Harmonic Distortion






Protection Functions

Parameter		Min.	Typ.	Max.	Notes
External Thermal Protection NTC	R1	-	7.81 kOhm	-	When R_NTC falls below R1, External Thermal Protection is triggered, reducing output current until R2 is reached.
	R2	-	4.16 kOhm	-	When R_NTC is less than R2, output current is reduced to the programmed “Protection Current Floor.”
	Protection Current Floor	10%loset	60%loset	100%loset	10%loset > Iomin (default setting is 60%)
		Iomin	60%loset	100%loset	10%loset ≤ Iomin (default setting is 60%)
Over Temperature Protection		Decreases output current, returning to normal after over temperature is removed.			
Short Circuit Protection		Auto Recovery. No damage will occur when any output is short circuited. The output shall return to normal when the fault condition is removed.			
Over Voltage Protection		Limits output voltage at no load and in case the normal voltage limit fails.			

Dimming

● DALI Dimming

The recommended implementation of the dimming control is provided below.



Implementation: DALI Dimming

● Time Dimming


Time dimming control includes 3 kinds of modes, they are Self Adapting-Midnight, Self Adapting-Percentage and Traditional Timer.

- **Self Adapting-Midnight:** Automatically adjusts the dimming curve based on the on-time of past two days (if difference <15 minutes), assuming that the center point of the dimming curve is midnight local time.
- **Self Adapting-Percentage:** Automatically adjusts the on-time of each step by a constant percentage = (actual on-time for the past 2 days if difference <15 min) / (programmed on-time from the dimming curve).
- **Traditional Timer:** Follows the programmed timing curve after power on with no changes.

● Output Lumen Compensation

Output Lumen Compensation (OLC) may be used to maintain constant light output over the life of the LEDs by driving them at a reduced current when new, then gradually increasing the drive current over time to counteract LED lumen degradation.

Programming Connection Diagram




Note: (1) The driver does not need to be powered on during the programming process.

(2) Both “OTP-” and “DA” (gray) should be connected to “Return” of the programmer when programming.

- Please refer to [PRG-MUL2](#) (Programmer) datasheet for details.

Mechanical Outline



RoHS Compliance

Our products comply with the European Directive 2011/65/EC, calling for the elimination of lead and other hazardous substances from electronic products.

Revision History

Change Date	Rev.	Description of Change		
		Item	From	To
2017-05-15	A	Datasheets Release	/	/
2017-10-25	B	Features	7 Years Warranty	Added
		Input Specifications	PF/THD	Updated
		General Specifications	Operating Case Temperature for Warranty Tc_w	Updated
2018-01-17	C	Output Specifications	No Load Output Voltage	Updated
		General Specifications	Lifetime	Updated
		Operating Case Temperature for Warranty Tc_w	+70°C	+75°C
		Lifetime vs. Case Temperature	/	Updated