

E	U	C	-	075	S	050	S	S	P	x	x	x	x
1	2	3	4	5	6	7	8	9	10	11			

1. Series 1 Alpha Character

- E Outdoor LED Driver
- L Indoor LED Driver
- H LED Driver for High Bay
- N Non-Isolated LED Driver

2. Input Range 1 Alpha Character

- U 90-305Vac
- A 90-305Va with 440Vac IOVP
- W 90-264Vac
- L 90-132Vac
- D 140-305Vac
- H 176-264Vac
- B 176-305Vac
- F 180-528Vac
- M 198-264Vac
- S 249-528Vac
- T 312-528Vac
- N 342-457Vac

3. Type 1 Alpha Character

- V Constant Voltage Output
- C Constant Current Output
- D, G, K Adjustable Output Current with Digital Interface
- B Adjustable Output Current with Potentiometer
- L Low Warranty
- R Round Shape Design with AOC Function
- S Short Case with Push Terminals
- P Adjustable Output Current with Dip-switch
- M Multiple Variances with AOC Function
- N Adjustable Output Current with NFC

4. Output Power 3 Numeric Characters

- 1K5 1500W
- 1K0 1000W
- 150 150W
- 075 75W
- 1W5 1.5W

5. No. of Outputs 1 Alpha Character

- S Single
- D Dual
- T Triple
- Q Quad
- P Pentad
- H Hexad

6. Output Voltage/Current 3 Numeric Characters

- 500 500V 15A 15.0A
- 200 200V 999 9.99A
- 050 50V 140 1400mA
- 025 25V 105 1050mA
- 2V5 2.5V 070 700mA
- 035 350mA

11. Modify 2 Alpha Character

- 00 Standard Product
- A0 Non-programmable Version
- C0 Class P model for EUD, EUG, ESD and LUD Series
- F0 0-5V Dimming Control
- L0 Extended Lifetime
- P0 Certificated to PSE Type 2
- P1 Certificated to PSE Type 1
- P2 Certificated to PSE Type 2, with 15kV Surge Protection
- P3 Certificated to PSE Type 1, with 15kV Surge Protection
- xx Customized

10. Product Code 2 Alpha Character

- xx Modified
- 00 Standard Product
- 10 Certificated to CCC
- 20 Certificated to KS
- 30 Certificated to BIS
- 40 Certificated to INMETRO

9. Case & Application Feature 1 Alpha Character

- Outdoor Products
- A New Enhanced Outdoor Product
- M Outdoor/Indoor Metal Case (Normal Rectangle)
- Y Outdoor/Indoor Extremely Cold Application down to -55°C
- F Indoor Long and Slim Metal Case
- C Outdoor/Indoor High Accuracy Output Current
- P Indoor Standard Plastic Case
- E Outdoor/Indoor Terminal Block
- R Indoor Round Case
- W Independent Indoor Standard Plastic Case with Terminal Block
- L Outdoor/Indoor Long Lifetime
- G Indoor Studs Box Type
- 2 New Enhanced Indoor Product

8. Input Cable Indicator 1 Alpha Character

- S Standard, 2 Pin, UL
- T Standard, 3 Pin, UL
- D Standard, 2 Pin, VDE
- F Standard, 3 Pin, Flying Leads
- V Standard, 3 Pin, VDE
- G Standard, 3 Pin, Global
- B Standard, 3 Pin, BIS

7. Options & Modes 1 Alpha Character

- S Standard (Non-dimming)
- R Triac Dimming Control
- D 0-10V with or without 0-5V/PWM/Timer
- T Timer Dimming
- W PWM Dimming
- C PWM Dimming and 0-10V Dimming
- B DALI with or without PWM/AC Dim/Push Dimming Timer
- G DMX512
- F On/Off Dimming/Step Dimming
- A AC Dimming
- L AC Power Monitoring and 0-10V/PWM/Timer with Dim-to-Off
- M 0-10V/PWM/Timer with Dim-to-Off