

LUD-030S100MTF

Dimmable Constant Current LED Power Supply

Inventronics LUD Power Supply is the reliable choice for linear and area fixtures for office - industrial – shop – retail

Benefits

- 1% dimming capability with Dim to Off
- Programming via Inventronics PC programmer / Tuner4TRONIC
- Very low ripple for high lighting quality
- 12V Aux included
- Long lasting and high reliability
- UL Class 2

Applications

Linear and area lighting
Office – industrial – shop – retail


Approbations & Certifications

FCC / cULus / Class P

In preparation, if not already printed on the label



CLASS P




Size	Unit	Inch	Millimeter
Case Length		11.02	280.00
Case Width		1.14	29.00
Case Height		1.02	26.00
Mounting Length		10.63	270.00
Connectors		UL, KF250-3.5, 250-402 Push Pin or equivalent	

Product Features

- 1% dimming capability incl. Dim to Off
- 0-10V / PWM dimming
- Low THD $\leq 20\%$ @ full load
- Input voltage: 120 – 277V
- Very wide ambient temperature range
- Programmable drivers
- Low flicker index $< 5\%$
- 12Vaux included
- Long lifetime up to 100k hours
- 5 years warranty



	Item	Value	Unit	Remarks
INPUT	Nominal voltage	120 – 277	V	
	Nominal frequency	50 / 60	Hz	Max 47 – 63Hz
	AC voltage range	108 – 305	V	
	Input current AC	0.32/0.14	mA	120, 277V
	Total Harmonic Distortion (THD)	≤ 20	%	120Vac / 270Vac output ≥ 60% load
	Stand-by power	2.0 max	W	30W Dim to Off
	Power factor	≥ 0.9		120Vac / 270Vac output ≥ 60% load
	Efficiency	Up to 85	%	Full load
	Leakage current	300 / 750	µA	120Vac/277 Vac / 60Hz Input, Output Full Load
OUTPUT	Inrush current max	3.32A / 15.1A	A	120Vac / 277Vac Typical / $t_{width} = 40 \mu s$ typical (max)
	Nominal voltage range	10 - 56	Vdc	59V max
	Maximum voltage	59	Vdc	120V-277Vac / 60Hz Input
	Nominal current range	350 – 1050	mA	
	Current accuracy	+/- 5	%	at 120-277Vac nominal voltage
	Flicker index	< 5	%	Full load
	Max. power	30	W	
	Start-Up Time	500	ms	120/277Vac / 60Hz Input, Output Full load
	DIMMING	Dimming technology	0-10V / PWM	
12V auxiliary output		10.8 / 12.0 / 13.2	V	Min./Typ./Max. – yellow wire
12V auxiliary current		200	mA	
0-10V dimming		0 / 10 / 15	V	Min./Typ./Max. – purple wire
Output source current		200	µA	Max. – purple Wire
ENVIRONMENT	Dimming range	1-100%	%	1% dimming capability
	Ambient temperature range t_a	-40 ... +50	°C	50W
	Maximum case temperature t_c	90	°C	
	Storage temperature range	-40 ... +85	°C	
	Relative humidity	5 ... 85	%	Not condensing
	Surge transient protection	2 4	kV	L-N; L-FG & N-FG
	Environmental rating	Indoor		
	IP rating	IP 20		
	Expected lifetime	50'000 100'000	h	$t_c = 80^\circ C$ $t_c = 70^\circ C$

Wiring diagram




Installation / wiring

Wire preparation:
0.5-1.5mm²




Only Solid wire with a cross section of 0.5 – 1.5 mm².
Strip 6mm of insulation from the cables to ensure perfect operation of terminals


Operating window




Efficiency vs power




PF vs power




THD vs power




Overtemperature protection behavior



0-10V dimming curve @ minimum dimming set to 1%



1-10V Dimming curve @ minimum dimming set to 1%



Programming & current setting

The screenshot shows a software interface for programming a device. At the top, there is a dropdown menu for 'Operating Mode' set to 'Default' and a text field for 'LUD-050S140MTF - Eng.Sample'. Below this, there is a section for 'Output Current' with several checked options: 'Constant Lumen', 'End of Life', 'Thermal Protection', and 'Dimming'. To the right, there are two panels: 'Current Mode' with a 'FixedCurrent' button, and 'Fixed Current' with three input fields: 'Minimum Current' (400 mA), 'Operating Current' (400 mA), and 'Maximum Current' (1400 mA).

Please use the Inventronics Programmer (Hardware) and Tuner4TRONIC (Software) to program current / features.
For further information please refer to www.tuner4tronic.com

Protections

- Output short circuit
- Output over current
- Over temperature protection
- Output over voltage

Programmable features

- Output current
- NTC
- Soft start
- Dim to off
- End-of-life indicator
- Dimming curve
- Constant lumen

Safety / EMC compliance

UL / cUL	UL8750, CSA-C22.2, Class 2, UL Class P
FCC	FCC Part 15 Subpart B, Class A
Ring Wave	NEMA SSL1

Ordering information

Part Number	Ordering Code / EAN (single)	Ordering Code / EAN (package)	Pieces / Package
LUD-030S100MTF	6977078992374	6977078992381	40

Inventronics
2825 S. Tulsa Avenue
Oklahoma City OK 73108
United States
www.inventronicsglobal.com

inventronics